

TECHNICAL DATA SHEET

Office Premium Cut-Size

Physical Parameters

	REFERENCE	TARGET	TYPICA	L VALUES
Basis Weight, g/m ²	ISO 536	105	101	109
Thickness, µm	ISO 534	120	116	124
Stiffness MD, mN	ISO 2493-1		≥ 170	
Stiffness CD, mN	ISO 2493-1		≥ 60	
Tensile MD, kN/m	ISO 1924-2		≥ 7.0	
Bendtsen Roughness, ml/min	ISO 8791-2	80	40	120
Air Permeability, ml/min	ISO 5636-3			≤ 1700
Moisture, %	ISO 287	4.0	3.5	4.5
Formation, #	Internal Method		≥ 40	

Optical Parameters

	REFERENCE	TARGET	TYPICAL	VALUES
Whiteness, CIE	ISO 11475	169	166	172
Brightness D65, %	ISO 2470-2	112	109	115
Opacity, %	ISO 2471	97	≥ 95	

Page:

1 / 1

Approved by:

Product Development and Technical Services: Eng. Vitor Crespo

sgftp / ftp_sheets FTP-PAP-0006 Rev.: 006 - Data: 2016/03/07 mfranca Printed on: 2016/11/28 21:04:54



QUALITY AND ENVIRONMENTAL INFORMATION

- The Navigator Company's papers are made from Elemental Chlorine Free (ECF) bleached kraft pulp;
- The Navigator Company's papers are produced in a neutral/slightly alkaline papermaking process, therefore considered as "acid free" products which meet the requirements of ISO 9706 standard, "Information and documentation – Paper for documents – Requirements for permanence";
- The Navigator Company's laboratories are accredited according to the ISO 17025 standard;
- Quality, Environmental and Safety Management Systems are certified according to the ISO 9001, ISO 14001 and OHSAS 18001 standards.
- The Navigator Company is chain-of-custody certified according to standards FSC-STD-40-004 and FSC-STD-40-005 (NC-COC-014433/NC-CW-014433) and to standard PEFC ST 2002:2013 (APCER/2007/CDR.0008).